



CS aerotherm®
Creative Technology in Baking
Since 1997

SET INTERNATIONAL STANDARDS IN BAKING

Our products are tried & trusted by
leading bakers around the world.



Email Us
contactus@csaerotherm.in

For Sales, Call
+91 80 40895000

Copyright 2021 © CS aerotherm Pvt Ltd

CS aerotherm stepped into the commercial bakery equipment domain, in the year 1997, with a long-term technical collaboration with FN Aerotherm, Denmark to manufacture rotary-rack (B-900 and B-1300) and electrical deck-ovens and most advanced Diesel, Gas, Electric Rotary Rack ovens. Today our product range not only meets the demand of domestic clients but also find their way to highly satisfied clientele in countries of Indian sub continent, Middle East and Africa. For the expanding domestic and international client database, our brand 'CS Ovens' stands for quality, variety and dependability.



Double Trolley Proofer

At CS aerotherm, we believe in helping our customers at every step of baking. We bring to you our bakery proofer which will help you in proofing and resting the dough at optimum temperature. We understand how crucial proofing the dough is. Be assured you will always get the perfect risen dough ready to be baked.

Production Capacity details per hour*

Model	Production	Capacities
B-700PC	Bread (400 g) in No.s / Kgs	480 / 192
B-700PC	Bun (45 g) in No.s / Kgs	1045 / 47
B-800PC	Bread (400 g) in No.s / Kgs	720 / 288
B-800PC	Bun (45 g) in No.s / Kgs	1568 / 288
B-900PC	Bread (400 g) in No.s / Kgs	1008 / 403
B-900PC	Bun (45 g) in No.s / Kgs	2016 / 91
B-1100PC	Bread (400 g) in No.s / Kgs	1260 / 504
B-1100PC	Bun (45 g) in No.s / Kgs	2940 / 132

* Bread requires 90 minutes for proofing and Bun requires 70 minutes for proofing. Proofing time will vary based on recipes.



B-700PC Proofer Specifications

Details	Specifications
Model	B-700PC
Trolley Size (W x D x H) in mm / inches	510 x 450 x 1580 / 20 x 18 x 63
Maximum Temperature (°C / °F)	50 / 122
Maximum Humidity (RH in %)	95
Installed Power (KW / HP)	2.6 / 3.5
Voltage and Phase (Volts / Phase / Hertz)	230 / 1 / 50
External Dimensions (W x D x H) in mm / inches	1250 x 1500 x 2000 / 50 x 59 x 79
Weight (Kgs)	200

Standard Tray Size in mm / inches is 450 x 450 / 18 x 18



B-800PC Proofer Specifications

Details	Specifications
Model	B-800PC
Trolley Size (W x D x H) in mm / inches	700 x 520 x 1580 / 28 x 20.5 x 63
Maximum Temperature (°C / °F)	50 / 122
Maximum Humidity (RH in %)	95
Installed Power (KW / HP)	2.6 / 3.5
Voltage and Phase (Volts / Phase / Hertz)	230 / 1 / 50
External Dimensions (W x D x H) in mm / inches	1250 x 1600 x 2000 / 50 x 63 x 79
Weight (Kgs)	250

Standard Tray Size in mm / inches is 450 x 700 / 18 x 27



B-900PC Proofer Specifications

Details	Specifications
Model	B-900PC
Trolley Size (W x D x H) in mm / inches	700 x 520 x 1907 / 28 x 20.5 x 75
Maximum Temperature (°C / °F)	50 / 122
Maximum Humidity (RH in %)	95
Installed Power (KW / HP)	2.6 / 3.5
Voltage and Phase (Volts / Phase / Hertz)	230 / 1 / 50
External Dimensions (W x D x H) in mm / inches	1250 x 1600 x 2200 / 50 x 63 x 87
Weight (Kgs)	300

Standard Tray Size in mm / inches is 450 x 45 / 18 x 18



B-1100PC Proofer Specifications

Details	Specifications
Model	B-1100PC
Trolley Size (W x D x H) in mm / inches	800 x 660 x 1907 / 31.5 x 26 x 75
Maximum Temperature (°C / °F)	50 / 122
Maximum Humidity (RH in %)	95
Installed Power (KW / HP)	2.6 / 3.5
Voltage and Phase (Volts / Phase / Hertz)	230 / 1 / 50
External Dimensions (W x D x H) in mm / inches	1250 x 1800 x 2200 / 50 x 71 x 87
Weight (Kgs)	350

Standard Tray Size in mm / inches is 450 x 450 / 18 x 18





CS aerotherm Pvt. Ltd

Address:

143 H, Bommasandra Industrial Area,
Hosur Road, Bangalore - 560 099, India.

Tel: +91 80 40895000

Email: contactus@csaerotherm.in

Web: www.csaerotherm.in

